

ISOLATING SWITCHES, EIS Series

EXPLOSION PROOF

BELGIUM



A QUALITY PRODUCT



APPLICATION

The EIS Isolating switches are suitable

- : for manual disconnecting means of small AC or DC appliances.
- : to prevent arcing of enclosed switches during connect and disconnect operation in zone 1,2 and zone 22 hazardous areas.

TECHNICAL DATA

Type of Protection	: Ex d IIA T6
Conforming to	: Standards IEC 60079-0 /1 or UL 60079-1
Marking for test	: Ex II2G
Degree of Protection	: IP65 acc.To IEC 60529
Ambient Temp. (Ta)	: -20° C to+ 55° C
Rated Voltage	: 400V.AC. 50/60Hz.
Electrical rating range	: 16 - 32A. 3 Poles
Protection class for UL.	: Class I, Division1 or 2 Group.C,D
	: Class II, Division 1 or 2 Groups.E,F,G
	: Zone1and Zone 2

CATALOGUE NUMBERS

Rating (Amp.) 3-Poles	Hub Size NPT (inch)	Cat.No.
16	3/4"	SIS 316
25	3/4"	SIS 325
32	1"	SIS 332

SPECIFICATION

Body, cover and operating	: Marine grade copper-free aluminium alloy with polyester powder coated, RAL 7032 (grey)
Bolts and mechanism	: Stainless steel

DIMENSION IN MM

